

MX60

Maximum Power Point Tracking Charge Controller

OutBack
Power Systems



- Active Maximum Power Point Tracking**
- High Operating Efficiency**
- Battery Voltages from 12 VDC to 60 VDC**
- PV Arrays up to 150 VDC Open Circuit**
- Negative or Positive Ground Systems**
- Built-in Data Logging**
- Standard 2 Year Warranty**

The MX60 is on the cutting edge of charge controller design. OutBack's real time active Maximum Power Point Tracking (MPPT) system ensures that your solar array is operating at its peak power point regardless of age, shading or environmental conditions. A peak operating efficiency of 98% maximizes your PV array's performance. The MX60's wide DC input range and 60 amp DC output current rating for 12, 24 or 48 VDC systems provides unmatched flexibility

in the wiring as well as the sizing of your solar array. The ability to step-down a high voltage solar array to a low voltage battery can save you money by reducing the size of wire required and making the installation simpler and faster.

All of the MX60's status information is displayed on the large built-in 3.1" (8 cm) backlit LCD screen and OutBack's exclusive system networking allows your MX60 to communicate with the rest of your OutBack products for complete integration and high performance operation. Monitoring the performance of your solar array investment is easy through the use of the built-in data logging system or via the MATE and optional PC software (available separately).

The MX60 is the only choice when you demand a high performance, efficient and customizable charge controller for your advanced power system.

MX60 Specifications

Nominal Battery Voltages		12, 24, 32, 36, 48, 54 or 60 VDC (Single model - selectable via field programming)
Output Current		60 amps maximum with adjustable current limit for smaller systems
Maximum Solar Array Size		12 VDC systems 800 Watts / 24 VDC systems 1600 Watts / 48 VDC systems 3200 Watts
PV Open Circuit Voltage (VOC)		150 VDC absolute maximum coldest conditions / 140 VDC start-up and operating maximum
Standby Power Consumption		Less than 1 Watt
Charging Regulation		Five Stages: Bulk, Absorption, Float, Silent and Equalization
Voltage Regulation Set points		10 to 80 VDC user adjustable with password protection
Equalization Voltage		Up to 5.0 VDC above Absorb Set point Adjustable Timer - Automatic Termination when completed
Battery Temperature Compensation		Automatic with optional RTS installed / 5.0 mV per °C per 2V battery cell
Voltage Step-Down Capability		Can charge a lower voltage battery from a higher voltage PV array
Power Conversion Efficiency	Typical	98% at 60 amps with a 48 V battery and nominal 48 V solar array
Status Display		3.1" (8 cm) backlit LCD screen with 4 lines with 80 alphanumeric characters total
Remote Interface		Proprietary network system using RJ 45 Modular Connectors with CAT 5e Cable (8 wires)
Data Logging		Last 64 days of operation - amp hours, watt hours and time in float for each day along with total accumulated amp hours, kW hours of production
Hydro / Wind Turbine Applications		Consult factory for approved turbines
Positive Ground Applications		Requires two pole breakers for switching both positive and negative conductors on both solar array and battery connections (HUB-4 and HUB-10 are not recommended for use in positive ground applications)
Operating Temperature Range		Minimum -40° to maximum 60° C (Power capacity of the controller is derated when above 25° C)
Environmental Rating		Indoor Type 1
Conduit Knockouts		Two ½" and ¾" on the back; One ¾" and 1" on each side; Two ¾" and 1" on the bottom
Warranty		Standard 2 year / Optional 5 year
Weight	Unit	11.6 lbs (5.3 kg)
	Shipping	14 lbs (6.4 kg)
Dimensions (H x W x L)	Unit	13.5 x 5.75 x 4" (40 x 14 x 10 cm)
	Shipping	18 x 11 x 8" (46 x 30 x 20 cm)
Options		Remote Temperature Sensor (RTS), HUB and MATE



Main Office:
 19009 62nd Avenue NE
 Arlington, WA 98223 USA
 Phone: (360) 435.6030
 Fax: (360) 435.6019

European Office:
 Urb. Garraf II Buzón 214
 08860 Les Botigues de Sitges
 Barcelona, ESPAÑA
 Phone: (+34) 600.843.845

www.outbackpower.com

Available From:

Renewable Energy New Brunswick
 2879 Route 124
 Kars, NB Canada E5T 2Y1
 Phone: 1-888-485-2249
 Fax: 1-888-485-2259
 Email: order@renewcanada.com
 Website: www.renewcanada.com